

Dynamic standing and balancing trainer
even for severely affected patients

balo



THERA-soft®
connectable+ 

THERA-Trainer balo

Item no. U001-100

● = Included ○ = Accessory

Name	Item no.	Included
Base unit	A002-308	●
Forefoot quick securing system	A002-345	●
Quick securing system for heels	A002-346	●
Balance unit long with low spring resistance	A002-926	●
Knee support set wide	A002-347	●
Pelvic support set	A002-350	●
Table unit with long vertical pipe	A002-310	●
Patient belt with bottom enlarged and leg straps, size L	A002-354	●
Electric lift system 115 V	A002-437	●
Feedback sensor type A including touch button	A003-881	●
Feedback sensor fixing set	A003-977	●
THERA-soft (Annual fee, first year included)	A006-630	●
Media station	A008-119	●
Tread extension set including ramp, magnetic	A004-273	○
Tread enhancement	A002-765	○
Knee support set	A002-671	○
Centre pad for pelvic support set	A003-726	○
Patient belt with bottom enlarged and leg straps, size S	A002-352	○
Patient belt with bottom enlarged and leg straps, size M	A002-353	○
Patient belt with bottom enlarged and leg straps, size XL	A002-355	○
Arm support cushion	A002-428	○
Upper body support	A002-356	○
Center cushions for upper body support	A002-357	○
Isolating transformer 115V	A004-002	○
Extended warranty balo	U009-100	○

Dynamic standing and balancing trainer
even for severely affected patients

balo

Product specifications	
Product description	THERA-Trainer balo is a non-powered training device that provides a safe environment to train standing and balancing (postural control) and generally redevelop muscles
Place of application	Suitable for use in enclosed spaces in facilities e.g. clinics, nursing homes, therapy practices or at the patient's home
Technical specification	<ul style="list-style-type: none"> - Dimensions (LxWxH): 46.5 x 30.7 x 37.4 - 49.2 inch Media Station additional: Tripod (LxWxH): 21.6 x 29.5 x 75.6 inch Display size diagonal 49" - Weight: approx. 170 lb Media Station additional: approx. 105 lb - Ambient conditions when in use: Temperature: : 41 °F to 104 °F Relative humidity: 5 % to 93 % Rh Air pressure: 700 hPa to 1060 hPa - Sound emission: LpA < 45 dB (A) - Technical details of the electric lift system: Power supply: 115 V~, 50/60 Hz Fuse protection: 2 x 2A slow-acting Protection class: II Degree of protection: Type BF Protection category: IP2X - Operational life: 10 years
Compatibility	THERA-soft
Patient requirements	<ul style="list-style-type: none"> - Patient weight: max. 308 lb - Patient height balance unit: 59.1 - 78.7 inch
Delivery and commissioning	<ul style="list-style-type: none"> - Transport and storage conditions: Temperature: -13 °F to 158 °F Relative humidity: 5 % to 93 % Rh Air pressure: 700 hPa to 1060 hPa - Commissioning: by authorised specialists
Service and maintenance	<ul style="list-style-type: none"> - Service: only by authorised service technicians - Maintenance: Balance unit: Replace after 5 years - Technical inspection: safety inspection every 24 months (manufacturer recommendation)
Registration	<ul style="list-style-type: none"> - Medical device class: I (USA) - CE marking: CE